

Lexmark XM5100 Series Monochrome Laser MFP



Model shown features additional options

Versatility and Solutions.



Mono



Duplex
Printing



Solutions



Duplex ADF
single-pass



Security



Up to
70 ppm



7-inch or
10.2-inch
Touch Screen



Fax



Direct USB
Port

LEXMARKTM

Lexmark XM5100 Series Key Features



XM5163 model with 550-sheet tray, 2100 sheet tray and caster base

Features that help you optimize your work



1) Intuitive color touch screen

Operate your device with ease through smart and intuitive navigation. Receive audible feedback when you use the touch screen.



2) Flexible media handling

Print on a wide range of media with built in 2-sided printing. Add additional input capacity to 3300 pages for higher volume printing needs.



3) Single-pass automatic document feeder

Save time by scanning both sides of your document in one pass with robust color-scanning capabilities and ultrasonic multi-feed detection to prevent jams.



4) Direct USB

The front USB port allows for convenient walk-up preview, and printing and is compatible with most printable image file formats.



5) Lexmark solutions

Reduce unnecessary printing and simplify work processes through solutions applications preloaded on your device. Choose additional Lexmark solutions to fit your unique workflow needs.



6) Lexmark's Unison™ Toner

Advanced toner science – powerful enough to deliver consistently outstanding image quality, with a shake free print system.



7) Eco-friendly features

Easy-to-access features like Eco-Mode to reduce paper and toner consumption, Sleep Button and Hibernate Mode make it easy to print responsibly and help you save energy.

Lexmark XM5100 Series Product Specifications



Product specifications

Lexmark XM5163

Lexmark XM5170

Product specifications		Lexmark XM5163	Lexmark XM5170
Printing			
Display	Lexmark e-task 7-inch (17.8 cm) color touch screen with audible feedback	Lexmark e-Task 10.2-inch (25.9 cm) color touch screen with audible feedback	
Print Speed: Up to	Black: 63 ppm	Black: 70 ppm	
Time to First Page: As fast as	Black: 4.4 seconds	Black: 4.0 seconds	
Print Resolution	1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 600 x 600 dpi		
Processor Speed	Dual Core, 800 MHz		
Memory	Standard: 512 MB / Maximum: 2560 MB	Standard: 1024 MB / Maximum: 3072 MB	
Hard Disk	Optional		
Recommended Monthly Page Volume ²	5000-25000 pages		
Maximum Monthly Duty Cycle: Up to ³	275000 pages per month	300000 pages per month	
Copying			
Copy Speed: Up to	Black: 63 cpm	Black: 70 cpm	
Time to First Copy: As fast as	Black: 4.2 seconds	Black: 4.0 seconds	
Reduce / Enlarge Range	25 - 400%		
Scanning			
Duplex Scan Speed: Up to	A4/Ltr, Black: 70 / 72 sides per minute - A4/Ltr, Color: 66 / 68 sides per minute		
Simplex Scan Speed: Up to	A4/Ltr, Black: 67 / 70 sides per minute - A4/Ltr, Color: 67 / 70 sides per minute		
Scanner Type	Flatbed scanner with ADF / DADG (single pass Duplex) / 150 pages 20 lb. or 75 gsm bond		
Optical Scanning Resolution	300 x 300 dpi (color), 600 X 600 ppi		
Faxing			
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps		
Supplies			
Laser Cartridge Yield	35,000 ¹ -page Toner Cartridge		
Cartridge(s) Shipping with Product	Up to 10000 pages ¹ Starter Toner Cartridge	Up to 25000 pages ¹ Starter Toner Cartridge	
Imaging Unit	100000 pages		
Paper Handling			
Paper Handling Standard	550-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 550-Sheet Input Tray		
Paper Handling Optional	250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Lockable Tray, 550-Sheet Lockable Tray		
Paper Input Capacity: Up to	Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 3300 pages 20 lb or 75 gsm bond		
Paper Output Capacity: Up to	Standard: 550 pages 20 lb or 75 gsm bond / Maximum: 1000 pages 20 lb or 75 gsm bond		
Media Types Supported	Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Refer to the Card Stock & Label Guide		
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, A6, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Oficio, Statement, Universal		
General			
Standard Ports	One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A), Gigabit Ethernet (10/100/1000)		
Optional Network Ports	Internal MarkNet™ N8350 802.11b/g/n Wireless		
Optional Local Ports	Internal RS-232C serial, Internal 1284-B Bidirectional Parallel		
Noise Level, Operating	Print: 57 dBA / Copy: 58 dBA / Scan: 57 dBA	Print: 58 dBA / Copy: 58 dBA / Scan: 57 dBA	
ENERGY STAR	Yes		
Specified Operating Environment	Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)		
Size (in. - H x W x D) / Weight (lb.)	47.4 x 24.05 x 25.9 in. / 247 lb.		

¹ Based on approximately 5% print coverage. Actual yields may vary based on factors such as page coverage, image type, job size, print/copy/fax modes, and duplexing.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.



Lexmark and Lexmark with the diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners. ENERGY STAR® is a U.S. registered mark. Information in this document is subject to change without notice. Unison is a trademark of Lexmark International, Inc. Information in this document is subject to change without notice.