

e-STUDIO™ 2008A

e-STUDIO™ 2508A

e-STUDIO™ 3008A

- > Black & White Multifunction Printer
- > Up to 30 PPM
- > Small/Medium Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



e-STUDIO™ 2008A/2508A/3008A

Main Specifications

| | |
|---------------------------------|--|
| Copy System | Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing |
| Display | 9" Color WVGA Touch Screen Tilting Display |
| Copy Speed | 20/25/30 PPM (LT) |
| First Copy Out | 4.3/4.3/4.3 |
| Warm-Up Time | Approx. 20 Seconds |
| Copy Resolution | 2,400 x 1200 dpi with Smoothing |
| Stack Feed Bypass | 3.9" x 5.8" to LD, Envelope |
| Multiple Copying | Up to 999 Copies |
| Paper Capacity | Standard 1,200 Sheets/Max. 3,200 Sheets |
| Original Feed | Optional 300-Sheet DSDf or 100-Sheet RADf |
| Scan Speed & Weights | DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Bond, Duplex: 9.3-110 lb Bond RADf Scan: Up to 73 IPM (Monochrome or Color): Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond LD |
| Max. Original Size | Drawer 1: 550 Sheets-ST-R to LD |
| Paper Feed Sizes | Drawer 2: 550 Sheets-ST-R to LD Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to LD Opt. 550-Sheet Paper Feed Pedestal-ST-R to LD Opt. 550-Sheet Drawer for PFP-ST-R to LD Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 550 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 100 Sheets-14 lb Bond-140 lb Index Opt. 550-Sheet Paper Feed Pedestal-16 lb Bond-140 lb Index Opt. 550-Sheet Drawer for PFP -16 lb Bond-140 lb Index Opt. Envelope Cassette for PFP-16 lb Bond-140 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type), 17-28 lb Bond Standard Automatic Duplex Unit (16 lb Bond-140 lb Index) |
| Paper Weights | |
| Duplex | |
| Reproduction Ratio | 25% to 400% |
| Max Duty Cycle | Max. 80K/100K/120K Month |
| Weight | Approx. 121 lb |
| Approx. Dimensions | 23" (W) x 23" (D) x 31" (H) |
| Toner Yield | 43.9K @ 5% |
| Power Source | 120 Volts, 50/60 Hz, 15 Amps |
| Power Consumption | Maximum 1.5kW (120V) |
| CPU | Intel Atom™ 1.33GHz (Dual-Core) |
| Memory | 4GB |
| Hard Disk Drive | 320GB Self-Encrypting Drive FIPS 140-2 Validated |

e-BRIDGE Next Print Specifications

| | |
|-------------------------------|--|
| PDL | PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG |
| Print Speed | 20/25/30 Pages Per Minute (LT) |
| Print Resolution | 600 x 600 dpi (1 bit) or 2,400 x 600 dpi (with Smoothing), 1,200 x 1,200 dpi (2 bit) or 3,600 x 1,200 dpi (with Smoothing) PS3 Only |
| Operating Systems | Windows® Vista, Windows Server® 2008/R2, Windows® 7, 8, 8.1, 10, Windows Server® 2012/R2, Macintosh® (Mac OS x 10.4, 10.5, 10.6, 10.7, 10.8, 10.9, 10.10, 10.11), Unix®, Linux® |
| Network Protocols | TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk® for Macintosh Environments |
| Printing Protocols | SMB, LPR/LPD, IPP (Ver.1.1) w/Authentication, AppleTalk PAP or EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP |
| Print Drivers | Windows® Vista SP2 (32-bit, 64-bit), Windows Server® 2008 SP2 (32-bit, 64-bit), Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8/8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows® 10 (32-bit, 64-bit), Mac OS® X 10.6.8, 10.7.4, 10.8, 10.9, 10.10 RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth |
| Interface | |
| Wireless Device | AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play) |
| Device Management | TopAccess, EFMS 6.2 (e-BRIDGE Fleet Management Software) |
| Account Control | Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function |
| Accessibility Features | Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts |



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408 EAL3+), IEEE2600.1, IEEE802.1X, Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp
* Compliant with IEEE2600.1 in High security mode.

Environmental Stds.

Energy Star (V2.0), EPEAT Gold, Blue Angel Mark (RAL UZ-171, MFD), Canadian ECP, Californian Proposition 65, Nordic Swan, RoHS
WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

Certification

Scan Specifications

| | |
|--------------------------|---|
| Scan Speed | DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADf Scan: Up to 73 IPM (Monochrome or Color) |
| Scan Modes | Standard: Full Color, Auto Color, Monochrome, Grayscale |
| Scan Resolution | 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi |
| File Formats | Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) |
| Image Compression | Color/Grayscale: JPEG (High, Middle, Low) |

Facsimile Specifications

| | |
|----------------------------|--|
| Compatibility | Super G3 |
| Data Compression | MH/MR/MMR/JBIG |
| Transmission Speed | Approx. 3 Seconds Per Page |
| Fax Modem Speed | Up to 33.6 Kbps |
| Memory Transmission | 100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job |
| Scan Speed | 0.7 Seconds Per Page, Maximum 73 IPM |

e-Filing Specifications

| | |
|--------------------------|--|
| Operation Method | Color Touch Screen Control Panel or Client PC |
| Number of Boxes | 1 Public Box, 200 Private User Boxes |
| Capacity of Boxes | 100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document |

Accessories (Options)

| | | | |
|---|----------|---------------------------------|-----------|
| Platen & Document Feeder Options | | | |
| DSDf | MR4000 | Meta Scan Enabler | GS1010 |
| RADf | MR3031 | IPsec Enabler | GP1080 |
| Platen Cover | KA5005PC | Unicode Font Enabler | GS1007 |
| | | Embedded OCR Enabler | |
| | | Single License | GS1080 |
| | | Five Licenses | GS1085 |
| Additional Paper Options | | Multi-Station Print Enabler | |
| Paper Feed Pedestal | KD1058 | Single License | GS1090 |
| Drawer Module | MY1048 | Five Licenses | GS1095 |
| Envelope Cassette Option | MY1049 | USB Hub Option | GR1270 |
| Large Capacity Feeder | KD1059LT | Advanced Scanning (ReRite) | GB1280V8 |
| | | SharePoint Connector | GB1440 |
| Finishing Options | | Exchange Connector | GB1450 |
| Inner Finisher | MJ1042 | Google Docs Connector | GB1540 |
| 50-Sheets Staple Finisher | MJ1109 | | |
| Saddle-Stitch Finisher | MJ1110 | Miscellaneous Options | |
| Hole Punch Unit for MJ1042 | MJ6011 | Stand | STAND5005 |
| Hole Punch Unit for MJ1109/MJ1110 | MJ6105 | Accessible Arm | KK2550 |
| Bridge Kit | KN5005 | Work Tray | KK5005 |
| Job Separator | MJ5014 | Harness Kit for Coin Controller | GQ1280 |
| Connectivity/Security Options | | | |
| FAX Unit/2nd Line for FAX Unit | GD1370 | | |
| Wireless LAN/Bluetooth | GN4020 | | |
| Bluetooth Keyboard | GR9000 | | |
| Accessory Tray | GR1250 | | |
| Panel 10-Key Option | GR1260 | | |
| Card Reader Holder | GR1290 | | |

Corporate Office

9740 Irvine Blvd., Irvine, CA 92618
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

9740 Irvine Blvd., Irvine, CA 92618
Tel: 949-462-6000

Web Site

www.business.toshiba.com

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1.